



SUPER CAST



- Super Cast is a proprietary process in which GFRC (Glass Fiber Reinforced Concrete) is utilized in conjunction with many different aggregates to obtain a realistic stone appearance.
- Super Cast contains polymers; these polymers give it flexibility, durability and strength.
 - Hairline cracks that may occur in the finished product are a natural characteristic of concrete. Hairline cracks do not affect the structural integrity of the concrete. Hairline cracks are defined as cracks that are less than 0.004” wide, which is the thickness of a piece of common copy paper. These cracks are not covered under warranty and are deemed acceptable.
- Each Super Cast Top is unique. Like natural stone it contains color patterns and surface characteristics that vary from one top to the next. All tops are verified acceptable by a certain criteria before they are shipped.
- Each Super Cast piece is factory sealed and ready for use. This sealer repels oil and water and creates a barrier against stains and mildew. It is suitable for exterior freeze/thaw areas on horizontal surfaces.
 - Oil or Grease should be removed immediately and not allowed to sit for a long period of time. Although the sealer will repel oil and or grease the sealer is not intended to be a permanent barrier.
 - Household staining agents such as mustard, wine, coffee and others should be removed as they are discovered. They will not immediately stain the surface but can damage if left unattended.
- It is suggested that annually a sealer is reapplied to protect against the elements and the occasional spill. Additional applications may be necessary if the product is washed frequently or the sealer has noticeably lost its repelling quality.